



starLine 7720

- Load capacity: 7 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- LED drum lighting
- Drum capacity: 60l
- Spin speed: 1500 rpm
- g Factor 605
- Residual moisture 44%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 35 profiClean and 24 freely programmable slots
- Door hinge right or left



starLine TC 7730

- Load capacity: 7 kg
- Large 4.3" colour display
- Stainless steel drum
- LED drum lighting
- Condensation system
- Drum capacity: 118l
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left

Company or brand name	Schulthess	
Type of appliance	Washing machine	
Type or sales description	starLine 7720	
Product number		
Model with drain pump (P)	7720.2PU	
Model with drain valve (V)	7720.2UV	
Application features		
Load capacity	max. kg	7
Drum capacity	l	60
Spinning speed	max. rpm	1500
g Factor	g	605
Residual moisture ¹⁾	%	44
Structural design		
Footed appliance with work surface	•	
Door hinge ³⁾	r/l/w	
Dimensions		
Height	cm	85
Width	cm	60
Depth including distance from wall	cm	67
Depth with door open (front loader)	cm	110
Height (adjustable)	cm	1
Weight when empty	kg	90
Equipment		
Detergent tank and drum	chrome-nickel steel	
Loading opening	Ø cm	34 / 180°
Automatic door opening	•	
Connecting cable	m	1,6
Drain:		
– Drain hose with benda, only model (P)	m	1,5
– Model with drain pump (P)	Ø mm	21
– Model with drain valve (V)	Ø mm	50
Electric power and water supply		
Electrical connection	400V 2N~ / 50Hz / 4,6kW / 10A	
Voltage / connected loads / fuse	230V 1N~ / 50Hz / 2,3kW / 10A	
Water connection		
– Pressure hose G ¾" with fine filter	m	1,5
– Can be connected to cold water / hot water	cold water / hot water 70 °C	
– Water pressure	bar	1–10
Options		
	– Door hinge left	
	– Hot water connection	
	– Drain valve or drain pump	
	– Connection for 8 liquid detergents with dosing pump	
	– Machine plinth	
	– Machine plinth with drawer for fluff filter	
Safety and service		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	

Explanations:

– Available or yes • Not available or no

1) Values determined in the 60°C cotton programme.

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

7) Information on switchover options can be found in the installation instructions, where required.

Note: State of the table details as 03.2021, subject to further developments.

Company or brand name	Schulthess	
Type of appliance	Condensation dryer	
Type or sales description	starLine TC 7730	
Product number	7730.2U	
Load capacity	max. kg	7
Structural form		
Footed appliance with work surface	•	
Standard unit for wash and dry column	•	
Door hinge ³⁾	r/l/w	
Dimensions⁴⁾		
Height	cm	85
Width	cm	60
Depth including space from wall	cm	64
Height for built-in installation	cm	85,5
Depth with door open	cm	122
Height adjustable	cm	2
Drying control		
By time selection ⁵⁾	•	
Automatic by electronic moisture detection ⁶⁾	•	
System and equipment		
Drying technology	Air condensation system	
Programme time display	•	
Load quantity display	•	
Automatic door opening	•	
Loading opening	cm	vorne, Ø 36 / 31 / 180°
LED drum lighting	•	
Connecting cable	m	1,5
Outlet hose	m	2 / Ø 22 mm
Condensate drainage in container / Drainage direct	•	
Exhaust line	–	
Maximum drainage height	m	1
Exhaust hose Ø 100 mm	m	–
Power supply		
Electrical connection ⁷⁾		
Voltage	V	400V 2N~ / 230V 1N~
Connected values	kW	2,8 / 2,1
Fuse protection	AT	10 / 10
Safety and service		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	

Explanations:

– Available or yes • Not available or no

3) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.

5) Set the degree of drying according to the laundry items, as shown in the operating instructions.

6) Degree of drying is maintained automatically.

7) Information on switchover options can be found in the installation instructions, where required.